






































			EZP-250	EZU-100	CSP-H50
Products					
Network Interface		Ethernet			
		Wireless LAN			
		PPP	○	○	○
		USB		○	○
User Interface		RS232			○
		RS422			
		RS485			
		TTL (UART)	○	○	
		I/O			
Hardware Type		External-type			○
		Board-type			
		Module-type	○	○	
Voltage		VOLTAGE 5V	○		○
		VOLTAGE 3.3V	○	○	
Configuration		ezConfig			
		ezSerialConfig			
		ezConfigMP			
		ezManager			
F/W upgrade		TFTP F/W Upgrade			
		Serial F/W Upgrade	○	○	○
Additional function		TELNET			
		MULTI PORT			
		EAP-MD5			
		Multi-Connection			
		SSL			
		SSH (Data)			
		SSH (Management)			
		DNS			
		DDNS			
		TELCOM			
		SLIP			
ETC		ISOLATION			
		Wide Range Temp			
		RoHS	○	○	○
Memory			ROM 64K RAM 4K	ROM 128K RAM 4K	ROM 128K RAM 4K
Protocols			TCP, UDP, IP, ICMP, PPP	TCP, UDP, IP, ICMP, PPP	TCP, UDP, IP, ICMP, PPP
Dimensions			34 x 20 mm	34 x 20 mm	89 x 57 x 24 mm