

Search ezTCP

MAC IP Serial

Local IP Address

10.10.10.92

50005

Read

Search Results

10.10.10.92

☒ View Comment

Network Serial Port Option

Product

CSE-M53N

Ver.:2.0A

Network

IPv4

Local IP Address

10 . 10 . 10 . 92

☒ Use static IP address☐ Obtain an IP Automatically(DHCP)☐ Obtain an IP Automatically(PPPoE)

Subnet Mask

255 . 255 . 255 . 0

Gateway IP Address

10 . 10 . 10 . 1

DNS IP Address

0 . 0 . 0 . 0

PPPoE ID

PPPoE Password

☐ Obtain DNS Server Address Automatically☐ Obtain an IP From The First Received Packet

IPv6

Disable

☐ Use static IP address☒ Obtain an IP Automatically

EUI

MAC Address

Local IP Address

Gateway IP Address

DNS IP Address

Search All

Write

Status

Simple Test

ezTCP Manager v3.3C (2016/03/31)

Advanced Menu

Tools

Search ezTCP

MAC

IP

Serial

Local IP Address

10.10.10.92

50005

Read

Search Results

10.10.10.92

View Comment

Network

Serial Port

Option

COM1

Serial Port

Serial Type

RS-232

TTL

☐

Baudrate

9600

Parity

NONE

Data Bits

8

Stop Bit

1 bit

Flow Control

NONE

☐ DTR/DSR

TX Interval

0

Create an ezVSP Port

TCP/IP

Communication Mode

T2S - TCP Server

Peer Address

Peer Port

0

Local Port

8000

☐ TCP Server

Event Byte

0

Timeout

300

Data Frame

Data Frame Interval(10ms)

0

Separator

Separator Length

0

Separator(HEX)

00000000

Separator Operation

Transmit Separators

☐ Telnet COM Port Control(RFC2217)

☐ Disable TCP Transmission Delay

☐ SSL

Search All

Write

Status

Simple Test

ezTCP Manager v3.3C (2016/03/31)

Advanced MenuTools

Search ezTCP

MACIPSerial

Local IP Address

10.10.10.9250005Read

Search Results

10.10.10.92

View Comment

NetworkSerial PortOption

Option

☒Telnet

☐Send MAC Address

☐SSL

☐SSH

☒IPv4 Address Search

☐Debugging Message

☐Multiple Connection

☐Power Management

Comment

ezTCP Firewall

☐Allowed MAC Address

☐Allowed IP Range

IPv4 Address

0000

Network Mask

0000

IPv6 Address

☐Apply To ezManager

Notify IPv4 Change

Protocol

Disable

Interval

0

Minute(s)

Port

0

Data Type

ASCII

DDNS ID

DDNS Password

Host Name(custom)

Search All

Write

Simple Test

Network Connections

Status

Status

FIRMWARE VERSION
CSE-M53N / 2.0 Rev.A (CSE-M53N_R20A.) / B10

SYSTEM UPTIME
0 days / 20:22:22.17

IP4 NETWORK INFORMATION
MAC Address - 00:30:f9:14:a6:b5
Device IP address - 10.10.10.92
Subnet mask - 255.255.255.0
Gateway - 10.10.10.1
Name Server - 0.0.0.0

TCP STATE
COM1 - LISTEN

SERIAL STATUS
COM1 sio_rx - 52 , net_tx - 52 , net_rx - 388 , sio_tx - 388

ARP TABLE
10.10.10.94 10:62:e5:a0:9e:d8 59 65534

TCP TIMER
Keep Alive - 10000ms
Disconnect - 2000ms

TCP/IP Connection

Name	TCP State
tty	LISTEN:23
com1	LISTEN:8000

Password

☐ Refresh Every 1 Second.

IP address Conflict Detection

Close

TCP TIMER
Keep Alive - 10000ms
Disconnect - 2000ms
Retransmission - 200ms
Delayed ACK - 20ms
Nagle - 40ms